

BELTING SELECTION

ROUND BELTING

		2mm	2.4mm	3/32"	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	9/16"	5/8"	3/4"									
		2mm	3mm	4mm	5mm	6mm	6.3mm	7mm	8mm	9mm	9.5mm	10mm	12mm	12.7mm	13mm	14mm	15mm	16mm	18mm	19mm	20mm	
Non-Reinforced Belting	POWERTWIST MOVE® Link Belting								●		●			●		●					●	
	Eagle® Blue 80 EC*	●		●	●	●	●		●		●	●										
	Eagle Clear 80 EC*	○		○	○	○	○		○		○	○										
	Eagle Blue 80 MD*				●	●	●	●	●		●	●		●	●		●		●			
	Eagle Opaque 80	○		○	○	○	○		○		○	○					○					
	Eagle Blue 85*			●	●	●	●		●		●	●					●					
	Eagle Clear 85*	○	○	○	○	○	○	○	○		○	○	○	○		○		○	○		○	○
	Eagle Orange 85*	●	●	●	●	●	●	●	●		●	●	●	●		●		●		●	●	●
	Eagle Orange 89 SureConnect™										●					●					●	
	Eagle Red 85*				●	●								●								
	Eagle Green 89	●		●	●	●	●		●	●		●	●	●			●		●		●	●
	Eagle Green 89 T	●		●	●	●	●		●	●	●		●	●			●		●		●	●
	Eagle Green 89 T SureConnect™											●	●				●		●		●	●
	Eagle Red 90	●		●	●	●	●	●	●	●		●	●	●	●		●	●	●	●		
	Eagle Beige 95*				○				○			○					○					
	Eagle Clear 95*		○	○		○		○		○		○		○		○		○		○		○
	Eagle White 40D			○	○	○	○		○		○						○		○		○	○
	Eagle Blue 55D											●					●		●			
	Eagle Blue 80 EC QC*				○	○			○		○											
	Eagle Blue 85 QC*				○	○			○		○	○										
	Eagle Clear 85 QC*				○	○	○		○		○	○		○	○		○		○		○	○
	Eagle Red 85 QC				○	○			○		○	○		○	○		○		○		○	○
	Eagle Yellow 85 QC*				○		○		○		○		○		○		○		○		○	○
	Eagle Clear 85 TOR				○																	
	Reinforced	Eagle Orange 85 R*					●	●		●		●	●	●	●		●	●		●	●	●
Eagle Hyfen 85 R†					●	●		●		●		●	●	●		●	●	●		●	●	
Eagle Green 89 R					●	●		●		●		●	●	●		●		●		●	●	
Eagle Green 89 RT					●	●		●		●		●	●	●		●		●		●	●	
Eagle Beige 95 R*																						
Eagle Can Cable†											●											
Eagle Fabricated Belts	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

Abbreviation Key

CXF	Co-extruded Flat	R	Reinforced
CXR	Co-extruded Ribbed	RCS	Reduced Contact Surface
EC	Regulation (EC) 1935/2004	RSGT	Reinforced SuperGrip Top
LCF	Low Coefficient of Friction	RT	Reinforced Textured
MD	Metal Detectable	SGT	SuperGrip Top
PU	PolyUrethane	T	Textured
PVC	PolyVinyl Chloride	TOR	Twisted O-Rings
QC	Quick-Connect	TPE	ThermoPlastic Elastomer

- Not all product in-stock, please call for availability.
- Some diameters and cross sections may be subject to minimum orders. Dimensions are for reference only.
- Flat belting available in Eagle Orange 85. Additional cross sections, colors, and durometers are available.
- Contact Applications Engineering at AE@fennerdrives.com for design assistance.

BELTING SELECTION

V BELTING

6mm x 4mm	8mm x 5mm	10mm x 4mm T-Top	3L	3L T-Top	3L Crown-Top	3L Twin	Z/10	A/13	AA	A Twin	A/13 Lo-Ridge-Top	A/13 Ridge-Top	A/13 Hi-Ridge-Top	B/17	BB	B/17 Ribbed	B/17 Wing-Top	B/17 Ridge-Top	C/22	C/22 Ribbed	C/22 Ridge-Top	D/32	D/32 Ribbed		
																								POWERWIST MOVE® Link Belting	Link Belting
																								POWERWIST MOVE Bridge Top™	
																								POWERWIST MOVE SGT PU	
																								POWERWIST MOVE SGT PVC	
																								POWERWIST MOVE RCS	
																								POWERWIST MOVE Friction Top®	
																								POWERWIST Antistatic¶	
																								POWERWIST Roller Drive™	
																								Eagle® Blue 80 EC*	
																								Eagle Clear 80 EC*	
																								Eagle Blue 80 MD*	
																								Eagle Opaque 80	
																								Eagle Blue 85*	
																								Eagle Clear 85*	
																								Eagle Ivory 85	
																								Eagle Orange 85*	
																								Eagle Red 85*	
																									Eagle Green 89
																									Eagle Red 90
																									Eagle Beige 95*
																									Eagle Clear 95*
																									Eagle White 40D
																									Eagle Blue 55D
																									Eagle Red 85 CFX
																									Eagle Ivory 85 SGT
																									Eagle Green 89 SGT PVC
																									Eagle Red 90 SGT PVC
																									Eagle White 40DSGT PVC
																									Eagle Opaque 80 R
																									Eagle Orange 85 R*
																									Eagle Hyfen 85 R*
																									Eagle Ivory 85 R
																									Eagle Green 89 R
																									Eagle Beige 95 R*
																									Eagle Hyfen 95 R*
																									Eagle Hyfen 85 CFX/CXR
																									Eagle Ivory 85 RSGT†
																									Eagle Fabricated Belts

* These belts are FDA compliant (unless cogged).
 † Can Cable available in Red 50D LCF, Blue 55D, Blue 55D Aramid, Natural 55D, Green 63D, and Natural 63D.
 ‡ Eagle Ivory 85 SGT and RSGT available with PVC, PU or TPE top surface.
 ¶ ISO 1813:1998 inspected and certified by Fenner Drives.